

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. H-22

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T15S R31E
SW 1/16
S12
1988
RLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 18" in the ground and raised a mound of stone around the pipe.

From Which:

A Pine 12" dia., Bears N15°E., 17.3 ft., scribed: SW1/16 S12 BT

A Pine 12" dia., Bears S54°W., 2.7 ft., scribed: SW1/16 S12 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North and West 4 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1960
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: March 17, 1988
Refer to Map of Survey No. 1034

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 28 day of Mar, 1988
Robert J. D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)