

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. L-22

**History of original corner establishment:**

Grant County Survey Records show no previous establishment of this Cor.

**DIAGRAM**

T15S R31E  
W1/16  
C-.-C  
S13  
1988  
RLS 848

**Description of corner evidence found:**

Grant County Survey Records show no previous establishment of this Cor.

**Description of monument and accessories | established to perpetuate the original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.

From Which:

A Pine 12" dia., Bears S11<sup>0</sup>W., 3.1 ft., scribed: CW 1/16 S13 BT

A Pine 14" dia., Bears N17<sup>0</sup>E., 8.8 ft., scribed: CW 1/16 S13 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North & East 3 ft. from the corner.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 12, 1980  
DOUGLAS M. FERGUSON  
848

This work is performed by:

Douglas M. Ferguson RLS 848

Mt. Vernon Oregon.

On: March 7, 1988

Refer to Map of Survey No. 1034

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 28 day of Mar, 1988  
Robert D. Gay by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)