

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. G

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

HWY
- - -
PVT:USFS
CL-NW1/4
1988
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

At the intersection of the N-S Center Line of the NW 1/4 of Section 11 and a Line 50 ft. Southerly from the Center Line of Highway 395, set the corner of USFS land

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.

From Which:

Set 5/8"x30" iron pins with plastic caps stamped PLS 848 and guard posts with warning and boundary signs South, 10.0 ft. and S81°E., 10.0 ft. from the corner.

Measurements to accessories taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1909
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: May 2, 1988
Refer to Map of Survey No. 1038

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 28 day of Mar, 1989
Robert D. Bazett by _____
(COUNTY OFFICIAL) (DEPUTY)