

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. R-7

History of original corner establishment:

Corner was originally established by
Bamford Robb, in July, 1880, under
General Land Office Contract No. 357.
The U.S. Surveyor Generals Notes State:
Set post for 1/4 sec. cor.

from which

A pine 18 in dia bears S50°E., 39 lks. dist.
A Pine 20 in dia bears N10°W., 68 lks. dist.

DIAGRAM

T15S R31E
S20
1/4--
S29
1987
RLS 848

Description of corner evidence found:

No trace of the original post is found

Found 26" Pine with healed over blaze on proper
face.

Found 24" Pine stump with scribing reads 1/4 BT
Set the 1/4 Cor. at Record S10°E., 44.9 ft. and
N50°W., 25.7 from the blaze faces of the above
trees then set the corner point midway between points
as determined at record measure from the above described
Bearing Trees.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 29" in the ground.

From Which:

A Pine 5" dia., Bears N16°W., 30.1 ft., scribed: X BT

A Pine 14" dia., Bears S16°W., 32.2 ft., scribed: 1/4 S29 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, North 3 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: April 14, 1987
Refer to Map of Survey No. 991

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 24 day of July, 1987
Douglas M. Ferguson by _____
(COUNTY OFFICIAL) (DEPUTY)