

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. T-2

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T15S R31E
W1/16
C--C
S30
1986
RLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the DIAGRAM, SET 22" in the ground.

From Which:

A Pine 9" dia., Bears N33°E., 21.5 ft., scribed: C-W 1/16 S30 BT

A Pine 6" dia., Bears S18°E., 11.2 ft., scribed: C-W 1/16 S30 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South & East 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Dec. 18, 1986
Refer to Map of Survey No. 977

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*30*..... day of.....*April*....., 19.....*87*.....
.....*Robert D. Baggett*..... by
(COUNTY OFFICIAL) (DEPUTY)