

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. T-5

History of original corner establishment:

Corner was originally established by Bamford Robb, in July, 1880, under General Land Office Contract No. 357. The U.S. Surveyor Generals Notes State: Set post for 1/4 Sec. Cor. with Pits and mound, as per instructions.

DIAGRAM

T15S R31E
1/4
S301929
1986
RLS 848

Description of corner evidence found:

No evidence of of original posts, pits or mounds is remaining.

This area has been under Beaver ponds, since the corner was originally established.
Set corner position at proportionate measure between corners 1/2 mi. North & South.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 30" in the ground.
From Which:
Set 5/8"x30" iron pins with plastic caps stamped SURVEY MARKER PLS 848, and metal guard posts with Bearing Tree, Warning & Boundary signs attached, as follows:
N89°36'W., 6.1 ft., and N 0°18'E., 6.2 ft., on the property lines.
Measurements to trees taken with an electronic tachimeter, with angles turned form the survey control network.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1963
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Dec. 18, 1986
Refer to Map of Survey No. 977

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*30*..... day of.....*April*....., 19.....*87*
.....*Robert D. DeGoff*..... by.....
(COUNTY OFFICIAL) (DEPUTY)