

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. T-9

History of original corner establishment:

Corner was originally established by
Bamford Robb, in July, 1880 under
General Land Office Contract No. 357.
The U.S. Surveyor Generals Notes State:
Set post for 1/4 sec. cor.

DIAGRAM

T15S R31E
1/4
S291S28
1987
RLS 848

from which:

A Pine 18 in. dia., bears N75°W., 40 lks. dist.
" " 12 " " " S60°E., 30 lks. dist.

Description of corner evidence found:

No trace of original post is found.

Found 22" Pine stump with blaze and scribing
reading part of the "1/4" visible, on the proper face
for the SE Bearing Tree.

Set the Corner position at record measure (N60°W.,
19.8 ft.) from the blaze face of the Bearing Tree.

**Description of monument and accessories I established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 28" in the ground.

From Which:

A Pine 12" dia., Bears N54°E., 25.2 ft., scribed: 1/4 S28 BT

A Pine 12" dia., Bears S26°W., 52.0 ft., scribed: 1/4 S29 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, North 2 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: April 14, 1987
Refer to Map of Survey No. 991

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 24 day of July, 1987
Robert D. Bisset by _____
(COUNTY OFFICIAL) (DEPUTY)