

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No V-7

History of original corner establishment:

Corner was originally established by
Bamford Robb, in July, 1880, under
General Land Office Contract No. 357.
The U.S. Surveyor Generals Notes State:
Set post for 1/4 sec. cor.

from which:

A pine 20" dia., bears N10°W., 78 lks. dist.
" " 24" dia., bears S15°E., 32 lks. dist.

DIAGRAM

T15S R31E
S29
1/4-.-
S32
1987
RLS 848

Description of corner evidence found:

No trace of the original post is found.

Found a 24" Pine stump with BT scribe visible,
on the proper face.
Set the corner position at record measure,
S10°E., 51.5 ft. from blaze face of stump.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 26" in the ground.

From Which:

A Pine 12" dia., Bears N 5°W., 11.7 ft., scribed: 1/4 S29 BT

A Pine 12" dia., Bears S42°E., 16.5 ft., scribed: 1/4 S32 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, North 2 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1980
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: April 14, 1987
Refer to Map of Survey No. 991

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 24 day of JULY, 1987
Robert D. Leggett by _____
(COUNTY OFFICIAL) (DEPUTY)