

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. W-5

History of original corner establishment:

Corner is originally established by Robert D. Baggett, PLS 598, in 1982 and shown on Map of Survey No. 720, of the Grant County Survey Records. The Legend of that map States: Set 5/8"x30" iron pin with attached plastic cap, marked B-G-A SURVEY MARKER.

DIAGRAM

T15S R31E
N1/16
S311S32
1986
RLS 848


Description of corner evidence found:

Found 5/8" iron pin with plastic cap stamped: B-G-A SURVEY MARKER.

No accessories are originally established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Replaced the above described 5/8" iron pin, as follows:
Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 28" in the ground.
From Which:
A Pine 8" dia., Bears N51°E., 16.7 ft., scribed: N1/16 S32 BT
A Pine 10" dia., Bears S53°W., 7.9 ft., scribed: N1/16 S31 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South & West 5 ft. from the corner.



This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Dec. 12, 1986
Refer to Map of Survey No. 974

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*30*..... day of.....*April*....., 19.....*87*.....
.....*Robert D. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)