

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T15S R31E

NE 1/16 S34

Description of corner evidence found:

NONE

See Record Map of Survey No. 938.

Description of monument and accessories I established to perpetuate the original location of this corner:

At corner point, I set a 2½x30 inch aluminum pipe with aluminum cap marked as shown 26 inches in the ground, from which I scribe new BT's:

A Pine, 5 inch diam. bears S. 40° E., 38.7 feet,
marked NE 1/16 S34 BT.

A Pine, 8 inch diam. bears S. 28° W., 29.5 feet,
marked NE 1/16 S34 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Robert D. Bagett
OREGON
JULY 12, 1963
ROBERT D. BAGETT
598

Cor. set by: R. D. Bagett
Witnesses : J. L. Watson
M. D. Bagett

June 5, 1986

NE 1/16 S34

1986

OPLS 598

Nailed brass washer marked OPLS 598 to lower blaze of new BTs.
Painted 6" red band around new BT's above blaze and on blaze
and attached BT signs and warning signs to BT's. Set steel fence
posts approx. 5 feet South and East from monument and attached appropriate
signs. Used magnetic compass with 18° 30' E. var. Used steel tape measuring
to a 40d nail driven in right side center at root crown of new BT's.

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the...22... day of...June... , 19.86
.....*Robert D. Bagett*..... by
(COUNTY OFFICIAL) (DEPUTY)