

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Y-3

History of original corner establishment:

Corner is originally established by Robert D. Bagett, PLS 598, in 1981 and shown on Map of Survey No. 681, of the Grant County Survey Records. The Legend of that map States: Set 5/8"x30" iron pin with attached plastic cap, marked B-G-A SURVEY MARKER.

DIAGRAM

T15S R31E
C
S1/161S31
C
1986
RLS 848

Description of corner evidence found:

Found 5/8" iron pin with plastic cap stamped:
B-G-A SURVEY MARKER.

No accessories originally established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Replaced the above described 5/8" iron pin, as follows:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 24" in the ground.

From Which:

Set 5/8"x30" iron pins with plastic caps stamped PLS 848 SURVEY MARKER, and guard posts with warning and bearing tree signs South 4.6 ft., and East 5.0 ft. from the corner.

Measurements to pins taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Dec. 12, 1986
Refer to Map of Survey No. 974

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*20* day of.....*April*....., 19.....*87*
.....*Robert D. Bagett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)