

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. M-1

History of original corner establishment:

In 1972, R.D. Baggett PLS 598 established this corner as shown on Map of Survey No. 274, of the Grant County Survey Records, That Map of Survey States :
Set 5/8"x30" iron Pin with attached plastic cap Marked BGF SURVEY MARKER.

DIAGRAM

T15S
R31E R32E
S1/16
S13/16
J987
RLS 848

Description of corner evidence found:

Found a 5/8" iron pin with plastic cap marked "BGF SURVEY MARKER." This pin is accordance with Map of Survey No. 274 of the Grant County Survey Records, as performed by R.D. Baggett, PLS 598.

Description of monument and accessories | established to perpetuate the original location of this corner:

At position of the above described 5/8" iron pin.
Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 24" in the ground.
From Which:
A Pine 7" dia., Bears N27°W., 21.9 ft., scribed: S1/16 SJ3 BT
A Pine 20" dia., Bears S37°E., 25.7 ft., scribed: SJ/16 S18 B1
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South & West 6 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1908
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Nov. 3, 1987
Refer to Map of Survey No. 1021

Office of Sauvage County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 28 day of Mar, 1987
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)