

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established in 1896, under Mineral Survey No. 316, by C.M. Foster, U.S. Dept. Mineral Surveyor. Mineral Surveyors Notes state:
To corner No. 2

A fir post 5ft. long, 4 inches square set 18" in the ground with mound of earth. Scribed COR NO. 2 MS NO 316
A Pine 30 inches in dia. Blaze and scribed COR NO 2 MS NO 316 BT bears N 55½°E 5½ft.
A fir 3 ft. in diam. blazed and scribed COR No. 2 MS NO 316 BT, bears S 31½°E 27ft. and the old location corner bears S 86°E 36½ft distance.

DIAGRAM

COR NO. 2
MS NO. 316
1982
PLS 848

Description of corner evidence found:

Found rotten remains of wood post in a mound of stone and earth.

From which

A Pine stump 34" dia., scribed but not legible

Bears N 55½°E, 5.5ft.

A rotten Fir snag, 5' high, scribed NO. 2 MS 316 BT

Bears S 31½°E 27.8ft.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown on the diagram, set 15" in the ground and raised a mound of stone and earth around the pipe.

From which

A fir 16" dia. Bears S 80°E 15.0ft. scribed COR NO 2 MS NO 316 BT

A fir 8" dia. Bears N 65°W 19.2ft. scribed COR NO 2 MS NO 316 BT

Nailed brass whshers stamped PLS 848, Bearing Tree signs and warning signs to each tree. Painted a red band around each tree.

Set steel posts with warning and Bdry signs. N 59° 30'W, 4ft. and S 6° 44'W 5' form cor.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 7-20-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 1 day of June, 1983
Robert D. Sigelt by _____
(COUNTY OFFICIAL) (DEPUTY)

Sec Map of Survey No. 750