

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established in 1896, under Mineral Survey NO. 316, by C.M. Foster, U.S. Dept. Mineral Surveyor. Mineral Surveyors notes state:

To cor NO. 3 which is the original center post on east end of claim and is a pine stump five feet high 16 inches diameter blazed on four sides and scribed COR NO. 3 MS NO. 316.
A Fir 8 inches in dia. blazed and scribed COR NO. 3 MS NO. 316 BT bears N 71½°E 16 ft.
A Fir 18 inches in dia. blazed and scribed COR NO. 3 MS NO. 316 BT, bears S 9½°E, 21 feet.

DIAGRAM

COR NO. 3
MS NO. 316
1982
PLS 848

Description of corner evidence found:

Found the remains of a pine stump.

From which

A Fir 21" dia. live, in good condition Bears N 70°E, 16.0ft. blaze healed over.
A Fir stump hole Bears S 9°E approx. 21ft.
Accepted pine stump hole as corner position.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown on the diagram. Set 25" in the ground and placed a ring of stone around the pipe.

From which

The original Bearing Tree, a 21" dia. Fir Bears N 70°E 16.5ft. scribed COR NO. 3 MS NO. 316 BT
A pine 13" dia. Bears N 11°W, 21.5ft. scribed COR NO. 3 MS NO. 316 BT
Nailed Brass washers, stamped PLS 848 and Bearing Tree and warning signs to each tree. Painted a red band around each tree.
Set steel posts with warning and Bdry signs, N 6°E 5ft. and S 6°W, 5ft from cor.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 7-20-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 1 day of June, 1983
Robert D. Baggett by Sec. of Survey No. 750
(COUNTY OFFICIAL) (DEPUTY)