

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established in 1896, under Mineral Survey NO. 316, by C.M. Foster, U.S. Dept. Mineral Surveyor. Mineral Surveyors notes state:

To corner NO. 4

A pine post 4½ feet long 4 inches square set 18 inches in the ground with mound of earth and rocks, scribed COR NO. 4 MS NO. 316.

A Fir 8 inches in dia. blazed and scribed COR NO. 4 MS NO. 316 BT bears N 27½°W 25 feet. A Fir 12 inches in dia. blazed and scribed COR NO. 4 MS NO. 316 BT, bears S 80½°E 25ft.

DIAGRAM

COR NO. 4
AMS NO. 316
1982
PLS 848

Description of corner evidence found:

Found rotten remains of wood post in center of an old mound of stone and earth.

Found rotted off post with scribing visible but not legible lying along side.

From which

A root hole Bears approx. N 27½°W 25ft.

Accepted rotted off post in mound as corner position

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½ aluminum cap, stamped as shown on the diagram. Set on solid rock and raised a mound of stone around the pipe.


From which

A Fir 12" dia. Bears N 29°W, 34.0ft. scribed COR NO. 4 MS NO. 316 BT

A tamarack 14" dia. Bear N 18°E, 24.2ft. scribed COR NO. 4 MS NO. 316 BT

Nailed brass washers stamped PLS 848 along with Bearing Tree and warning signs to each tree. Painted a red band around each tree.

Set steel posts with warning and Bdry signs N 7°E, 5ft. and N 60°W, 5 ft. from cor.



Corner monumented 7-20-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 1 day of June, 1983
Douglas M. Ferguson by See Map of Survey No. 750
(COUNTY OFFICIAL) (DEPUTY)