

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established in 1896, under Mineral Survey No. 316, by C.M. Foster, U.S. Dept. Mineral Surveyor. Mineral Surveyors notes state:

To corner NO. 5
A Fir Post 5 feet long 4 inches square. Set 18 inches in the ground with mound of earth and stone, scribed COR NO. 5 MS NO. 316.
A Fir 22 inches in dia. blazed and scribed COR NO. 5 MS NO. 316 BT, bears N 5°E 20 feet.
A Fir 20 inches in dia. blazed and scribed COR NO. 5 MS NO. 316 BT bears S 24°E 29 ft.

DIAGRAM

COR NO. 5
MS NO. 316
1982
PLS 848

Description of corner evidence found:

No evidence of the original corner monument found.

From which

Found 30" Fir, live, in good condition with grown over blaze facing record for COR NO. 5
Set cor. position at Record Bearing and Dist from Tree.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with 3½" aluminum cap, stamped as shown on the diagram. Set 14" in the ground and raised a mound of stone and earth around the pipe.

From which

A Fir (The original Bearing Tree) 30" dia. Bears S 24°E, 30.0ft. scribed COR NO. 5 MS NO. 316 BT.
A Fir 18" dia. Bears N 86°W 19.2ft. scribed COR NO. 5 MS NO. 316 BT
Nailed brass washers stamped PLS 848, along with warning and Bearing Tree signs to each tree, Painted a red band around each tree.
Set steel posts with warning and Bdry signs S 60°E 5' and N 83½°W 5' from cor.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

Corner monumented 7-20-82
Witnessed by D. Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 1 day of June, 1983
Robert D. Beyer by _____
(COUNTY OFFICIAL) (DEPUTY)

See map of Survey No. 750