

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. 0-1

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

31E T15S R32E
N1/16
S241S19
1987
RLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories established to perpetuate the original location of this corner:

The Corner is on solid rock outcropping, set a 3-1/2" Brass Tablet, with brass foot, in concrete, at the corner point, on the solid rock. Stamped Cap as shown on the **DIAGRAM**

From Which:

A Pine 16" dia., Bears S88°W., 47.4 ft., scribed: N1/16 S24 BT
Chiseled an "X" in the solid rock East 3.0 ft. for the Sec. 19 Accessorie.
Measurements to accessories taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of tree. Painted a 6" red band at breast ht. around tree. Set steel fence posts with warning 1/2 Boundary Signs, south from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1960
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Nov. 6, 1987
Refer to Map of Survey No. 1021

Office of... *Surveyor* ... County of... *Grant* ...
State of... *Oregon* ... I hereby certify that the within instrument was filed in this office
for record on the... *28* day of... *Mar* ... 19... *89* ...
... *Robert A. Boyd* ... by ...
(COUNTY OFFICIAL) (DEPUTY)