

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. LINE TREE
History of original corner establishment:

Line Tree was originally established by Samuel W. Lackland, in 1881, under General Land Office Contract No. 384. The U.S. Surveyor Generals Notes State: 30.68 chains, Pine 30 in. dia.

DIAGRAM



T15S R32E
LINE TREE
S191S20
1987
RLS 848

Description of corner evidence found:

Found 40"+ Pine snag & root wad lying next to the root wad hole. The center of the said hole conforms nearly exactly to record measurements. Said hole is accepted as the original Line Tree Position.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the center of the above described root wad hole, Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 28" in the ground.
From Which:
A Pine 12" dia., Bears S28°W., 52.8 ft., scribed: S19 LINE TREE BT
A Pine 14" dia., Bears S45°E., 41.4 ft., scribed: S20 LINE TREE BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 1 ft. from the corner.



This work is performed by:
Douglas M. Ferguson, RLS 848
Mt. Vernon Oregon.
On: Oct. 9, 1987
Refer to Map of Survey No. 1016

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*7*..... day of.....*May*....., 19.....*88*.....
.....*Robert H. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)