

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-9

History of original corner establishment:

Corner was originally established by Samuel W. Lackland, in 1881. under General Land Office Contract No. 384. The U.S. Surveyor Generals Notes State: Set stone 16x7x6 in mound of stone for 1/4 sec. cor.

DIAGRAM

T15S R32E
1/4
S201S21
1987
RLS 848

from which

A pine 24 in. dia. bears N87°W., 36 lks. dist.

Description of corner evidence found:

The original stone is not identified.

Found a 42" Pine with "4 S" scribing visible. in opened blaze. Accepted this tree as the original Bearing Tree and established the 1/4 Cor. at Record Measure of S87°E.. 23.8 ft. from the blaze face.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap. stamped as shown on the **DIAGRAM**, SET 26" in the ground. From Which: (New Bearing Trees)
A Pine 8" dia.. Bears S64°W., 3.7 ft., scribed: 1/4 S20 BT
A Pine 6" dia.. Bears S80°E., 29.9 ft., scribed: 1/4 S21 BT
Measurements to trees taken with a metal tape and magnetic compass. with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe. Bearing Tree Sign above blaze. and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South & West 2 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1963
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Oct. 7, 1987
Refer to Map of Survey No. 1016

Office of..... *Samuel* County of..... *Grant*
State of..... *Oregon* I hereby certify that the within instrument was filed in this office
for record on the..... *7*..... day of..... *May*....., 19..... *88*.....
..... *Robert V. Baggett* by
(COUNTY OFFICIAL) (DEPUTY)