

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. R-4

History of original corner establishment:

Corner was originally established by R.D. Baggett, in 1976, as shown on Map of Survey No. 398, of the Grant County Survey Records. That map states, that he set a 5/8"x30" iron pin at the corner position.

DIAGRAM

T15S R32E
S19
E1/4-.-
30
1987
PLS 848

Description of corner evidence found:

Found 5/8" iron pin as established by PLS 598, in 1976. See Map of Survey No. 398, as filed in the Grant County Survey Records.

Description of monument and accessories | established to perpetuate the original location of this corner:

At the position of the above described iron pin,
Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 29" in the ground.
From Which:
A Pine 14" dia., Bears S19°W., 29.6 ft., scribed: E1/4 S30 BT
A Fir 14" dia., Bears West , 87.6 ft., scribed: E1/4 S19 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Since the corner falls near a house, no post is placed near the monument.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1953
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson RLS 848
Mt. Vernon Oregon.
On: Nov. 5, 1987
Refer to Map of Survey No. 1021

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*28* day of.....*Nov*....., 19.....*87*
.....*Robert D. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)