

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Not previously established.

DIAGRAM

T15S R32E
E1/16 $\frac{S20}{S29}$
1983
PLS848

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the

original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap, stamped as shown in diagram.
Set 20" in the ground, & placed a ring of stone around pipe .

From Which:

A Pine 8" dia. bears N10°W, 3.0 ft. scribed E1/16 S20 BT.

A Pine 9" dia. bears S72°W, 11.3 ft. scribed E1/16 S29 BT.

Nailed brass washers stamped PLS848, bearing tree & warning sign to each tree.

Set steel posts with warning & boundry signs 5.0 ft. East & 5.0 ft. North from corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Corner monumented 4-6-83

Witnessed by D. Mitchell Ferguson

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of Surveyor County of Grant
State of Oregon , I hereby certify that the within instrument was filed in this office
for record on the 6 day of June , 1983
Robert D. Baxter by _____
(COUNTY OFFICIAL) (DEPUTY)

See map of Survey No. 773