

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Not previously established.

DIAGRAM

T15S R30E
NE 1/16
S29
1983
PLS848

Description of corner evidence found:

Not previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with 3½" aluminum cap, stamped as shown in diagram.
Set 20" in ground and placed a ring of stone around pipe.
From Which:
A Fir 10" dia bears N72°W, 4.3 ft. scribed NE 1/16 S29 BT.
A Fir 12" dia. bears N78°E, 6.2 ft. scribed NE 1/16 S29 BT
Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree
Set steel posts with warning & boundry signs east & south 5.0 ft from corner

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1958
DOUGLAS M. FERGUSON
848

Corner monumented 4-6-83

Witnessed by MD Mitchell Ferguson

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 1 day of June, 1983
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)