

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX NO. U-9

History of original corner establishment:

Corner was originally established by
R.D. Baggett, PLS 598, in 1976.
Refer to Map of Survey No. 398 of the
Grant County Survey Records, which states:
Set 5/8"x30" iron pin.

DIAGRAM

T15S R32E
S 1/16
S291S28
1988
RLS 848

Description of corner evidence found:

Found 5/8" iron pin as established by PLS 598 in
1976 and shown on Map of Survey No. 398 of the
Grant County Survey Records.

There are no accessories indicated on Map of Survey
No. 398.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 12" in the ground, replacing the 5/8" iron pin, and
raised a mound of stone and earth around the pipe.


From Which:

A Pine 6" dia., Bears S88°E., 16.2 ft., scribed: S1/16 S28 BT

A Fir 14" dia., Bears S33°W., 13.5 ft., scribed: S1/16 S29 BT

Measurements to trees taken with metal tape and magnetic compass with
20° East declination set off.

Nailed a brass washer stamped RLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, South 20 ft. & West 12.3 ft. from the corner:



This work is performed by:

Douglas M. Ferguson PLS 848

Mt. Vernon Oregon.

On: April 13, 1988

Remonumentation

Witnesses: D. Mitchell Ferguson & Ken Delano

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 28 day of Mar, 1989
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)