

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 725 dated March, 1901.

Intersect S bdy of T14S, R34E, 15.60 chs. west of the cor. of Ts.14S, Rs34 & 35E. I destroy all marks on old T. cor. referring to Ts 15S., Rs. 34 & 35 E and Set a basalt stone 20x12x12 ins. 16 ins. in the ground for closing cor. of Ts15S., R34 & 35E marked CC on S face and with 6 notches on S, E & W edges, from which

A pine 8 ins diam bears S58½°E, (21.1')32 lks dist. marked T15SR35E S6 BT

A pine 10 ins diam bears S42½°W, (35.6')54 lks dist. marked T15SR34E S1 BT

T14S R34E
S36

S 1 | S 6
R34E R35E
T15S
CC
1990

Description of corner evidence found:

Found the stone with the proper markings set firmly in the ground.

Ponderosa pine (Down & Rotting Away)(Blaze in Rotted Remains)(1901 BT) bears at record from the stone

14" Ponderosa pine (Good Condition)(Blaze Healed Over)(1901 BT) bears at record from the stone. Did not tie the BT to the new monument.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, N0°09'05"W, 21.61 feet from the stone to the township line as determined by survey. Built a mound of rock & earth to be 30" in diameter by 4" high around the monument, from which new BTs and Accessories are:

8" Douglas-fir bears S34°E, 8.6 feet scribed T15SR35E S6 CC BT

10" Douglas-fir bears S12°15'W, 10.6 feet scribed T15SR34E S1 CC BT

A Silver DEEP bears N12°15'E, 2.2 feet buried 6" in the ground

A Pink DEEP bears N34°W, 2.2 feet buried 6" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 4.2 feet W and 20.7 feet S of the corner adjacent to the original corner stone on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the W post.



I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 5, 1990, I established the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Robert D. Bayless
Grant County Surveyor



MAP OF SURVEY No. 1197