

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Homer D. Angell, US
Deputy Surveyor, during the original survey
Contract No. 725 dated March, 1901.

Set a basalt stone, 15x12x8 ins., 10 ins. in the
ground for cor. of secs 20, 21, 28 & 29, marked
with 2 notches on the S. and 4 notches on the E.
edges from which

- A fir, 8 ins. diam., bears S1°E, 21 lks. dist., marked T15SR34E S28 BT
- A pine, 12 ins. diam., bears S25°W, 14 lks. dist., marked T15SR34E S29 BT
- A pine, 12 ins. diam., bears N78°W, 18 lks. dist., marked T15SR34E S20 BT
- A pine, 8 ins. diam., bears N29°E, 33 lks. dist., marked T15SR34E S21 BT

DIAGRAM

T15S R34E

S20	S21
S29	S28

1987
PLS 699

Description of corner evidence found:

The corner falls in an old skid road and the original stone was not found.

13° White fir (Fair Condition)(Blaze Opened by Others)(1901 BT) bears S84° 30'E, 14.6 feet. Apparently the bearing should have been S89°E on the original notes.

12° Lodgepole pine (Dead & Down)(Scribing Visible)(1901 BT) bears at record

Position of the found and down 12° pine, (1901 BT) not determinable because it drug down the hill by the logging operation.

Position of the found and down 12° pine, (1901 BT) not determinable because of the badly rotted condition.

**Description of monument and accessories I established to perpetuate the
original location of this corner:**

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the
diagram, 26" in the ground, at the point determined by the bearing trees.
Built a mound of rock & earth to be 30" in diameter by 4" high around the
monument, from which new BTs are:

- 16° White fir bears S18° 15'W, 13.9 feet scribed T15SR34E S29 BT
- 9° White fir bears N58° 15'W, 15.7 feet scribed T15SR34E S20 BT
- 11° Douglas-fir bears N9°E, 51.8 feet scribed T15SR34E S21 BT

Attached BT and Attention signs to and painted a red band around each BT.
Bearings were turned from the control traverse with a theodolite, basis of
bearing being a solar observation, to stamped brass washers nailed in the
scribed red-painted blazes. Distances were measured from a 60d spike,
with an aluminum washer stamped PLS 699, which was driven into the side of
each BT approximately one foot above the ground.

Set steel fence posts 5 feet E and 5 feet W of the corner on the National
Forest Wilderness lines. Attached Wilderness Boundary signs to each post
and an Attention sign to the E post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877,
do hereby certify that on October 24, 1987, I
monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 12 DAY OF Nov, 19 87

Robert D. Bayart
Grant County Surveyor

