

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner was established by George R. Campbell, US Deputy Surveyor, during the original survey Contract No. 724 dated September, 1900.

Set an iron stone 18x14x6 ins. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on W face from which

A black pine 12 ins diam bears S1°W, (141.9')215 lks dist marked 1/4 S4 BT

A white fir 10 ins diam bears N36°E, (24.4')37 lks dist marked 1/4 S3 BT

Corner was maintained by Howard E. Taylor, RPE 2891, during a retracement survey dated August, 1957.

Found original marked stone. Original 12" B. Pine S1°W 215 lks., now stub windfall with scribe. Original 10" W. Fir N36°E 37 lks., rotted and gone.

We scribed new BTs: This corner is about 250 ft. N5°E from a 40" Diam. black pine with old line blazes on it.

14" Bl. Pine S7°W, 138.8 ft.

8" Bl. Pine S62°E, 41.0 ft.

**Description of corner evidence found:**

Found the marked stone set firmly in the ground in a rock mound and the two Taylor bearing trees.

15" Lodgepole pine (Good Condition)(Scribing Visible)(1957 BT) bears S5°15'W, 139.0 feet.

13" Lodgepole pine (Good Condition)(Scribing Visible)(1957 BT) bears S63°45'E, 39.6 feet.

12" black pine (1900 BT) not found. 10" white fir (1900 BT) not found.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock to be 30" in diameter by 4" high around the monument, from which new Accessories are:

An Orange DEEP bears N63°45'W, 2.8 feet and buried 8" in the ground

A Silver DEEP bears N5°15'E, 2.4 feet and buried 14" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped aluminum washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 4.2 feet S and 4.1 feet N of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the S post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 16, 1991, I monumented the corner as herein described.

**FILED**

**IN THE OFFICE OF THE Grant COUNTY SURVEYOR**

**THIS 30 DAY OF NOV, 1992**

*Robert D. Bays*  
Grant County Surveyor

**DIAGRAM**



**T15S R35E**

**1/4**

**S 4 | S 3**

**1991**

**PLS 699**



MAP OF SURVEY No. 1197