


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 725 dated March, 1901.



- Set a basalt 15x12x6 ins. 10 ins. in the ground for cor. of secs 1, 6, 7 & 12 marked with 1 notch on the N and 5 notches on the S edges from which
- A pine 12 ins diam bears S32°E, (23.1')35 lks dist. marked T15SR35E S7 BT
- A pine 12 ins diam bears S66°W, (31.7')48 lks dist. marked T15SR34E S12 BT
- A tamarack 18 ins diam bears N2°W, (69.3')105 lks dist. marked T15SR34E S1 BT
- A fir 14 ins diam bears N34°E, (106.9')162 lks dist. marked T15SR35E S6 BT

1990

Corner was maintained by Howard E. Taylor, RPE 2891, during a PLS 699 retracement survey dated August, 1957.

Found orig. single stone--no mound (On West boundary R35E) The orig. 12" pine S32°E, 35 lks is barely standing with scribe visible. Orig. 12" pine S66°W is rotted windfall partial scribe visible. The 18" Tam recorded N2°W is actually only 2° North of due west and hence true bearing is N88°W. (It is now standing snag with scribe visible). The 14" fir recorded N34°E is actually 34° north of due east and the true bearing is N56°E. This fir is now about 30" diam. and is green and the top is broken out about 30 ft. high. I scribed new BTs as follows:

- 32" Fir S10°E, 32.5 feet S7 BT
- 9" B. Pine N60°E, 14.1 feet S 6 BT
- 12" B. Pine S71°W, 31.4 feet S 12 BT
- 30" Fir N27°W, 61.0 feet S 1 BT

Description of corner evidence found:

Found the stone with the proper markings firmly set in the ground. A forest fire moderately burned the area around this corner location between my preliminary traversing and the setting of the corner monument. Fire line about 50' SE.

- 12" Lodgepole pine (Dead & Down & Badly burned)(Scribing Visible)(1901 BT) bears at SW record.
- 22" Western larch (Dead & Down)(Scribing Visible)(1901 BT) bears N88°W, 67.6 feet. See Taylor note about bearing. The BT was nearly completely burned by the forest fire.
- Was White fir snag that has totally burned and is in the dozed fire trail (1901 BT) bears N55°45'E, 107.6 feet. No evidence of the tree exists after the fire.
- 32" White fir (Poor Condition)(Scribing Visible)(1957 BT) bears S12°15'E, 32.8 feet. Attention sign is about 8' high on back of BT.
- 13" Lodgepole pine (Fair Condition)(Scribing Visible)(1957 BT) bears S70°15'W, 30.8 feet. The tree is badly scorched, but may survive.
- 30" White fir (Fair Condition)(Scribing Visible)(1957 BT) bears N26°45'W, 62.6 feet. The tree is somewhat scorched.
- 12" pine (1901 BT) and 9" B. Pine (1957 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 24" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound of rock & earth to be 30" in diameter by 6" high around the monument.

7" Western larch bears N59°15', 59.0 feet scribed T15SR35E S6 BT

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 4.9 feet N, 4.5 feet E, 4.7 feet S and 4.9 feet W of the corner on the National Forest and Strawberry Wilderness boundary lines. Attached Forest Boundary signs to the N and E posts and Wilderness Boundary signs to the S and W posts and an Attention sign to the N and E posts.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on September 9, 1990, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Homer D. Angell
Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers
OREGON
JULY 9, 1965
LELAND LEE MYERS
699

MAP OF SURVEY No. 1197