

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner was established by George R. Campbell, US Deputy Surveyor, during the original survey Contract No. 724 dated September, 1900.

Set an iron stone 28x20x15 ins. 15 ins. in the ground for 1/4 sec. cor. marked 1/4 on N face from which

A white fir 10 ins diam bears N18°E, (91.4')138½ lks dist. marked 1/4 S6 BT

A white fir 22 ins diam bears S15°W, (12.5')19 lks dist. marked 1/4 S7 BT

Corner was maintained by Howard E. Taylor, RPE 2891, during a retracement survey dated August, 1957.

Found Orig. marked stone measures 17x11x10 instead of 28x20x15 as recorded. Both original firs are red firs rather than white and are in good condition, the NE one now being 18" and the S one now being 28". Both bearings and BTs match orig. notes and ring count in scar overgrowth verifies they are orig. BTs, but distance to NE BT is only 13.0 ft. instead of 138½ lks. as recorded.

**Description of corner evidence found:**

Found a stone with the proper markings set firmly in the ground.

13" White fir (Fair Condition)(Blaze Healed Over)(1900 BT) bears N19°E, 17.5 feet. See Taylor note about the distance.

15" Douglas-fir (8' Broken Stub)(Scribing Visible)(1900 BT) bears S16°45'W, 13.5 feet.

DIAGRAM

T15S R35E

S 6  
1/4—  
S 7

1990  
PLS 699

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound of rock & earth to be 30" in diameter by 4" high around the monument, from which new BTs and Accessories are:

6" White fir bears S34°30'W, 17.7 feet scribed 1/4 S7 BT.

A Blue DEEP bears S19°W, 2.3 feet buried 9" in the ground

A Silver DEEP bears N34°30'E, 2.0 feet buried 8" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 4.9 feet E and 5.1 feet W of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the E post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on September 9, 1990, I monumented the corner as herein described.



FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

*Robert O. Baker*

Grant County Surveyor



MAP OF SURVEY No. 1197