

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by George R. Campbell, US Deputy Surveyor, during the original survey Contract No. 724 dated September, 1900.

Set a basalt stone 20x10x8 ins. 15 ins. in the ground for cor. of secs 2, 3, 10 and 11, marked with 5 notches on the S and 2 notches on the E edges from which

- A white fir 15 ins diam bears S58°30'E, (55.4')84 lks. dist marked T15SR35E S2 BT
- A black pine 20 ins diam bears S65°13'E, (35.0')53 lks. dist marked T15SR35E S11 BT
- A white fir 9 ins diam bears S82°30'W, (4.0')6 lks. dist marked T15SR35E S10 BT
- A white fir 9 ins diam bears N3°30'W, (25.1')38 lks. dist marked T15SR35E S3 BT

DIAGRAM

T15S R35E

S 3	S 2
S10	S11

1991
PLS 699

Description of corner evidence found:

Found the marked corner stone, two BTs and root holes for the other two BTs. This corner falls in the Glacier Complex forest fire and all trees are dead.

- Root hole (1900 BT) bears at SE record
- 14" fire killed Lodgepole pine (Dead)(Scribing Visible)(1900 BT) bears S66°E, 35.4 feet.
- Root hole (1900 BT) bears at SW record
- 12" fire-killed Alpine fir (Dead)(Scribing Visible)(1900 BT) bears N2°15'W, 25.0 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound with earth & rock to be 30" in diameter by 4" high around the monument, from which new BTs are:

- 9" fire-killed and sawed off Alpine fir bears N68°E, 7.7 feet scribed T15SR35E S2 BT
- 10" fire-killed and sawed off Alpine fir bears S57°15'W, 39.8 feet scribed T15SR35E S10 BT

Sawed off the dead BTs about 6' above the ground. Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped aluminum washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5.6 feet W and 5.4 feet N of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the W post.


I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 15, 1991, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Robert D. Baggett
Grant County Surveyor



MAP OF SURVEY No. 1197