

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 725 dated March, 1901. Set a trap rock 14x16x6 ins. 10 ins. in the ground for 1/4 sec. cor. marked with 1/4 on W face from which

- A tamarack 18 ins diam bears S22½°E, (42.9')65 lks dist. marked 1/4 S7 BT
- A tamarack 18 ins diam bears S65½°W, (45.5')69 lks dist. marked 1/4 S12 BT

Corner was maintained by Howard E. Taylor, RPE 2891, during a retracement survey dated August, 1957.

Found orig. "trap rock" with orig. marking. The orig. marked portion cracked off of orig. stone and is about size and shape of a piece of pie. I set a new stone 22x8x8 with ¼ on East alongside orig. stone and with its marked portion and built a stone mound around orig. and new stones. This c running NE and is 100 ft. more or less below the spring where this tiny stream heads. The 18" tam S22½°E, 42.9 ft. is now ok 22" with scribe visible. The other orig. tam is rotted windfall. I scribed

24" Tam S37°W, 63.5 feet 1/4 S12 BT

Description of corner evidence found:

Found the original and subsequent stones in a rock mound in a small stream flowing out of a nearby spring. A forest fire severely burned the area around this corner location between my preliminary traversing and the setting of the corner monument.

- 19" Western larch (Poor Condition)(Blaze Healed Over)(1901 BT) bears S24°15'E, 44.3 feet.
- 20" Western larch (Poor Condition)(Blaze Healed Over)(1957 BT) bears S33°30'W, 61.5 feet. Both BTs are badly scorched by the fire, but there is a hope for survival.
- 18" tamarack (1901 BT) not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 22" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock to be 48" in diameter by 8" high around the monument, from which new Accessories are:

- No new bearing trees set because all trees have been killed by the forest fire.
- An Orange DEEP bears N24°15'W, 3.3 feet buried 10" in the ground
- A Silver DEEP bears N33°30'E, 4.8 feet buried 10" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5.4 feet N and 4.5 feet S of the corner on the Strawberry Wilderness boundary lines. Attached Wilderness Boundary signs to each post and an Attention sign to the N post.


I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on September 10, 1990, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Robert D. Bayless
Grant County Surveyor



MAP OF SURVEY No. 1197