

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 725 dated March, 1901. Set a trap rock 12x10x6 ins. 8 ins. in the ground for 1/4 sec. cor. marked with 1/4 on W face from which

- A pine 20 ins diam bears West, (23.8')36 lks dist. marked 1/4 S13 BT
- A pine 20 ins diam bears East, (22.4')34 lks dist. marked 1/4 S18 BT

DIAGRAM

**T15S
R34E R35E**

**1/4
S13 | S18**

**1990
PLS 699**

Description of corner evidence found:

Found a stone with the proper markings set firmly in the ground. A forest fire severely burned the area around this corner location between my preliminary traversing and the setting of the corner monument.

- Rotten mass(Down & Rotting Away before fire)(1901 BT) beared at West record All the tree remains were burned by the fire.
- Lodgepole pine (Dead & Down)(Scribing Visible before fire)(1901 BT) beared at East record All the tree remains were burned by the fire.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound of rock to be 30" in diameter by 4" high around the monument, from which new BTs and Accessories are:

- 12" fire killed and sawed-off Alpine fir bears S40°15'E, 23.2 feet scribed 1/4 S18 BT
- 11" fire killed and sawed-off Alpine fir bears S28°45'W, 35.1 feet scribed 1/4 S13 BT
- An Orange DEEP bears N40°15'W, 2.2 feet buried 10" in the ground
- A Silver DEEP bears N28°45'E, 2.0 feet buried 12" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 4.7 feet N and 4.1 feet S of the corner on the Strawberry Wilderness boundary lines. Attached Wilderness Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on August 25, 1990, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Robert D. Bayless
Grant County Surveyor



MAP OF SURVEY No. 1197