

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by George R. Campbell, US Deputy Surveyor, during the original survey Contract No. 724 dated September, 1900.

Set a basalt stone 28x12x8 ins. 20 ins. in the ground for 1/4 sec. cor. marked 1/4 on N face from which

A black pine 10 ins diam bears S40°E, (7.3') 11 lks dist. marked 1/4 S19 BT

A white fir 18 ins diam bears N70°W, (4.6') 7 lks dist. marked 1/4 S18 BT

DIAGRAM

T15S R35E

S18

1/4—

S19

1990

PLS 699

Corner was maintained by Howard E. Taylor, RPE 2891, during a retracement survey dated August, 1957.

Found orig. marked stone and built stone mound around same. Both orig. BTs are standing snags with scribes visible. I scribed new BTs as follows:

10" Fir S52°E, 24.6 feet "S 19" "1/4 S"

12" Tam N19°W, 14.4 feet "S 18" "1/4 S"

Description of corner evidence found:

Found the marked stone firmly set in a mound of rock. A forest fire severely burned the area around this corner between my preliminary traversing and the setting of the corner monument.

Found before the fire, but now totally burned (1900 BT) beared at record

18" white fir was a leaning snag, but totally burned in the fire (1900 BT) beared at record

11" fire-killed Alpine fir (Dead)(Scribing Visible)(1957 BT) bears S55°15'E, 24.9 feet.

15" Western larch (Poor Condition)(Scribing Visible)(1957 BT) bears N21°15'W, 14.7 feet. The BT is scorched, but expected to survive.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 24" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock to be 30" in diameter by 6" high around the monument, from which new BTs and Accessories are:

10" Lodgepole pine bears S58°E, 94.3 feet scribed 1/4 S19 BT

A Blue DEEP bears S21°15'E, 2.7 feet buried 8" in the ground

An Orange DEEP bears N55°15'W, 2.6 feet buried 10" in the ground

Sawed off the dead BT about 6' above the ground. Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped brass washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5.2 feet W and 5.0 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the W post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on August 25, 1990, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF NOV, 1992

Robert D. Bazar

Grant County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

MAP OF SURVEY No. 1197