

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881, by Eugene P. Mc Cornack, Under General Land Office Contract No. 398. Surveyor Generals Notes State: Set basalt stone 14 x 8 x 8 ins. 10 ins in the ground for $\frac{1}{4}$ sec cor. marked $\frac{1}{4}$ on W face and raised a mound of stone alongside. Pits unpractical.

DIAGRAM


T15S
R36E R37E
 $\frac{1}{4}$
S25
1983
PLS 848

Description of corner evidence found:

No evidence found. N-S fence through area has displaced or destroyed all evidence.
No accessories originally established.
Set corner position by proportion.
(See narrative on map of survey)

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with a 3 $\frac{1}{2}$ " aluminum cap stamped as shown in diagram.
Set 20" in ground & placed a ring of stone around pipe.
From which:
A Juniper 7" dia. bears N82°W, 41.0 ft. scribed $\frac{1}{4}$ S25 BT.
Set steel posts with warning & boundary signs North 3 ft. & South 3 ft.
Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree.



Date June 17, 1983

Witnessed by D Mitchell Ferguson

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th. day of.....August....., 1983.
Robert H. Baggett by
(COUNTY OFFICIAL) (DEPUTY)