

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P. McCornack, Under General Land Office Contract No. 398. Surveyor Generals Notes State: Set basalt stone 14x12x12" 10" in the ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on N face .

From Which:

A Pine 10" dia. bears N25°W, 31 lks dist. marked $\frac{1}{4}$ S BT.
A " 40" " " S50°E, 29 " " " " " "

DIAGRAM

T15S R36E
S25
 $\frac{1}{4}$ S36
1983
PLS848

Description of corner evidence found:

Found a 12"x10"x9" stone set in ground with faint marks on North face. An old cluster of stone alongside.

From Which:

A Pine stump 40" dia. with scribing visible, bears S50°E, 19.1 ft. to blaze face.

A Pine, live and in good condition bears N15°W, 20.8 ft.

Accepted position of stone as corner position.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3 $\frac{1}{2}$ " aluminum cap stamped as shown in diagram. Set 18" in the ground, set original stone South alongside pipe & raised a mound of stone around pipe.

From Which:

A Pine 16" dia. bears S7°W, 23.9 ft. scribed $\frac{1}{4}$ S36 BT.

A " " " " (original bearing tree) N15°W, 20.8 ft. (new scribing) $\frac{1}{4}$ S25 BT.

Set steel posts with warning & boundry signs East 5 ft. & West 5 ft.

Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Corner monumented 6-23-83

Witnessed by Mollee Ferguson

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....

State of...Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 29th. day of.....August....., 1983.

Robert D. Beyer

(COUNTY OFFICIAL)

(DEPUTY)