

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P. McCornack, Under General Land Office Contract No. 398. Surveyor General's Notes State: Set basalt stone 24x14x10" 18" in the ground for corner to sections 25, 30, 31, and 36, marked with 5 notches on N and 1 notch on S edges, and raised a mound of stone alongside. Pits impractical.

DIAGRAM

T15S
R36E R37E
S25
S361983
PLS848

Description of corner evidence found:

Found stone 20"x14"x10" with 1 notch on S & 5 notches on N., set in the ground. No accessories originally established, accepted position of the stone as corner.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram. Set 8" in ground, set original stone South alongside & raised a mound of stone & earth around pipe.

From which:

A Juniper 14" dia. bears N33°W, 85.0 ft. scribed S25 BT.

A Post with warning & bearing tree signs bears West 5.0 ft.

Nailed brass washers stamped PLS848 to the tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Corner monumented 6-29-83

Witnessed by D. Mitchell Ferguson

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the.....29th..... day of.....August....., 19.....83.
[Signature] by
(COUNTY OFFICIAL) (DEPUTY)