

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P. Mc Cornack, Under General Land Office Contract No. 398. Surveyor Generals Notes State: Set basalt stone 22 x 12 x 6 ins. 16 ins. in the ground for standard cor. to secs. 34 & 35 marked SC with 2 notches on E and 4 notches on W edges and raised amound of stone alongside. Pits inpractical.

DIAGRAM

T15S R36E
S C
S34 | S35
1983
PLS 848

Description of corner evidence found:

No evidence of original stone found.
Found 24" Pine snag with scribing visible, reads 34.
Found 20" Pine, live in good condition with scribing, reads 36 S3 BT.
Found down & dead Pine with upper and lower blazed.
There are no trees of record, however these trees are original trees that where not recorded. Since the blazes of all trees face the proportion position that position is accepted as the standard corner.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with 3½" aluminum cap stamped as shown in diagram.
Set 12" in the ground & raised a mound of stone around the pipe.
From which:
A Pine 11" dia. bears N8°W, 5.4 ft. scribed T15S R36E S34 SC BT.
A Fir 9" dia. bears N69°E, 31.8 ft. scribed T15S R36E S35 SC BT.
Set a steel post with warning sign North 5 ft.
Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Date June 14, 1983

Witnessed by D. Mitchell Ferguson

OREGON
JULY 12, 1963
DOUGLAS M. FERGUSON
848

Office of.....Surveyor..... County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 29th day of August, 1983.
..... by
(COUNTY OFFICIAL) (DEPUTY)