105

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A Fullerton under his General Land Office Contract No. 395.

Surveyor General's records state:

Set basalt stone 15 x 13 x 6 in stone mound for ¼ sec. cor.

DIAGRAM

T15S R26E

S9

¼ ——·——

S16

Description of corner evidence found:

Found basalt stone 15 x 12 x 6 in stone mound. Found no visible marks on stone.

N.A.
Found old blaze facing corner in North fork of twin Juniper, S25°W 53.7' from corner.
Found old blaze facing corner in 12" Juniper, N74°E 25.9' from corner.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½" x 30" alum. pipe with 3" alum. cap marked as shown.
Buried stone next to pipe.

T15S R26E

S9

¼ ——·——

S16

RLS 1104 1979

A Juniper, 6 in. dia., bears N73°W 46.3', scribed ½ S9, B.T.
A Juniper, 11 in. dia., bears S6°E 130.2', scribed ¼ S16, B.T.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
James R. Tye
OREGON
JULY 22, 1977
JAMES R. TYE
1104

Witness to corner: Larry Wiley
Larry Wiley
L.S.I.T.

I hereby certify the above corner monument was re-established as herein described on 6/5/79.

Office of Surveyor County of Grant
State of Ore. , I hereby certify that the within instrument was filed in this office for record on the 23 day of August, 1979, at 1:30 o'clock P.m., (signed)
Robert H Bagott by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)

J-11