CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office Contract No. 395.

Surveyor General's records state:

Set basalt stone 16 x 12 x 7 in stone mound for cor. to sec.s 9, 10, 15 & 16. from which:
A Pine 30 in. diam. brs N5°E 28 lks.
" " 34 " " " N10°W 30 " .

DIAGRAM

T15S R26E

S9	S10
S16	S15

Description of corner evidence found:

Found stone 16 x 11 x 7 in stone mound with 3 notches on East edge and 4 hacks on South Side.

Fallen Pine snag, N10°W 19.9', scribed B.T. Fallen Pine snag, N5°E 18.0', scribed T15 R26 S10, B.T. (E. & S. omitted).
Note: bearings and distances are approximate.

Description of monument and accessories I established to perpetuate the original location of this corner

Hit solid rock 12" deep. Marked "X" in rock, set 2½" x 30" alum. pipe with 3" alum. cap over "X", set original stone next to pipe and built stone mound around pipe. Alum. cap is marked as shown:

T15S R26E

S9	S10
S16	S15

RLS 1104 1979

A Ponderosa Pine, 6 in. dia., bears N38°W 41.9', scribed T15S R26E S9, B.T.
A Ponderosa Pine, 8 in. dia., bears N10°E 49.6', scribed T15S R26E S10, B.T.
A Ponderosa Pine, 7 in. dia., bears S44°E 33.1', scribed T15S R26E S15, B.T.
A Ponderosa Pine, 7 in. dia., bears S51°W 61.3', scribed T15S R26E S16, B.T.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
James R. Tye
OREGON
JULY 22, 1977
JAMES R. TYE
1104

Witness to corner: Larry Wiley
Larry Wiley
L.S.I.T.

I hereby certify the above corner monument was re-established as herein described on 6/6/79.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of Aug., 1979, at 1:30 o'clock P.m., (signed)
Robert D. Baggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)