CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office contract No. 395.

Surveyor General's records state:
Set basalt stone 15 x 10 x.6 in stone mound for cor. to secs. 10, 11, 14, & 15.

DIAGRAM

T15S	R26E
S10	S11
S15	S14

Description of corner evidence found:

Found stone 15 x 10 x 5 in large stone mound. Found no identificable notches on stone.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½" x 30" Alum. pipe with 3" Alum. cap marked as shown. Buried original stone next to pipe and built stone mound around pipe.

T15S	R26E
S10	S11
S15	S14
RLS 1104	1979

A Juniper, 11 in. dia., bears N8°W 127.2', scribed T15S R26E S10, B.T.
A Juniper, 14 in. dia., bears N39°E 147.9', scribed T15S R26E S11, B.T.
A Juniper, 8 in. dia., bears S48°E 180.8', scribed T15S R26E S14, B.T.
A Juniper, 10 in. dia., bears S56°W 102.8', scribed T15S, R26E S15, B.T.

Witness to Corner: Michael Yardley
Chainman

REGISTERED PROFESSIONAL LAND SURVEYOR
James R. Tye
OREGON
JULY 22, 1977
JAMES R. TYE
1104

I hereby certify the above monument was re-established as herein described on 6-28-79.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of Aug., 1979, at 1:30 o'clock P.m., (signed)
Edward D. Barrett
(COUNTY OFFICIAL) by (DEPUTY)

Form R6-7100-57 (9/66)

T-17