CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. L-11

History of original corner establishment:

Corner not previously established

DIAGRAM
T15S R26E
C1/4
S16
1985
PLS 848

Description of corner evidence found:

Corner not previously established

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" galvanized iron pipe with 2-1/2" brass cap stamped as shown on the **DIAGRAM**, set 6" in the ground and raised a mound of stone and earth around the pipe.
From Which:
A Pine 12" dia., Bears S 6°W., 33.7 ft., Scribed: C1/4 S16 BT
A Pine 8" dia., Bears N88°E., 28.0 ft., Scribed: C1/4 S16 BT
Nailed brass washer stamped PLS 848 on blaze above BT Scribe, Bearing Tree Sign above balze and painted a 6" red band around each tree.
Measurements to trees taken with metal tape and bearings taken with magnetic compass with 20° Dec. set of to the East.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner is set June 10,1985
By Douglas M. Ferguson PLS 848
Ferguson Surveying & Engineering
Mt. Vernon Oregon.
Witnessed by J.David Brinton PLS 2065

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 2 *day of* July, 1985
Robert D. Burgett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

SEE MAP OF SURVEY NO. 870

Form R6-7100-57 (9/71)

☆ GPO—798-276

L-11