CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office contract No. 395

Surveyor General's records state:

"Set basalt stone 15" X 14" X 7" in stone mound for corner to Secs. 15,16, 21, & 22."

DIAGRAM

T15S S16	R26E S15
S21	S22

Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2" x 30" alum. pipe with a 3" alum. cap marked as shown set by double proportionate measure. Built mound around monument. New bearing trees tagged with brass washer marked "L.S. 981" and are described as follows:
A 12" juniper bears N3° 04'W, 42.2 ft. scribed T15S R26S S16 BT.
A 12" juniper bears N37°36"E, 154,8 ft. scribed T15S R26E S15 BT.
A 9" juniper bears S37° 29'E, 70.8 ft. scribed T15S R26E S22 BT.
A 10" juniper bears S66° 00'W, 116.28 ft. Scribed T15S R26E S21 BT.

T15S S16	R26E S15
S21 RLS 981	S22 1981

REGISTERED PROFESSIONAL LAND SURVEYOR
H. Leon Kennedy
OREGON
JULY 14, 1972
H. LEON KENNEDY
981

Witness to corner: David B. Clawson

I hereby certify the above corner monument was set as herein described.

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 25 *day of* Feb, *19* 8.
Robert D Baggett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO 799-509

N-13