CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office contract No. 395.

Surveyor General's records state:
Set basalt stone 16 x 13 x 4 for $\frac{1}{4}$ sec. cor. from which:
A Fir 22 in. diam. brs. N 70° W 44 lks.
" " 30 " " " S 89° E 22 lks.

DIAGRAM

T15S R26E

S15

$\frac{1}{4}$ —·—

S22

Description of corner evidence found:

Found stone 16 x 13 x 4 marked $\frac{1}{4}$ on top. Corner is approximately 2 chains East of the South Fork of Wind Creek as per the original notes.

A Doug. Fir, 32 in. dia., bears N69°W 30.7'. Blaze is open but scribes not visible.
A Doug. Fir snag, 32 in. dia., bears East 15.0', bark scribed $\frac{1}{4}$S, B.T. Opened snag, but found not scribed.
Both trees have BLM B.T. signs (7/8/59).

Description of monument and accessories I established to perpetuate the original location of this corner

T15S R26E

S15

$\frac{1}{4}$ —·—

S22

RLS 1104 1979

Set $2\frac{1}{2}$" x 30 Alum pipe with 3" Alum. cap marked as shown:

A Doug. Fir, 10 in. dia., bears N 23°E 29.5', scribed $\frac{1}{4}$ S15, B.T.
A Doug. Fir, 7 in. dia., bears S53°E 11.3', scribed $\frac{1}{4}$ S22, B.T.

Michael J. Yardley

Witness To Corner: Michael Yardley
Chainman

REGISTERED
PROFESSIONAL
LAND SURVEYOR
James R. Tye
OREGON
JULY 22, 1977
JAMES R. TYE
1104

I hereby certify the above monument was re-established as herein described on 6-20-79.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of Aug, 1979, at 1130 o'clock A.m., (signed)
Edward Bagot by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)

N-15