CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A Fullerton under his General Land Office Contract No. 395.
Surveyor General's records state:
"Set basalt stone 12 x 12 x 4 in stone mound for ¼ Sec. Cor.

DIAGRAM

T15S R26E
¼ S22
—•—
S27

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½" x 30" alum. pipe with 3" alum cap marked as shown:
Set by single proportionate measure. Built stone mound around monument.
A 10" Juniper bears N68 56'W, 121.95 feet scribed ¼ S22 BT
A 10" Juniper bears S38 39'W, 103.90 feet scribed ¼ S27 BT

T15S R26E
¼ S22
—•—
S26 27
RLS 981 1980

REGISTERED
PROFESSIONAL
LAND SURVEYOR
H. Leon Kennedy
OREGON
JULY 14 1972
H. LEON KENNEDY
981

Witness to corner: David B. Clawson

I hereby certify the above monument was set as herein described.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 25 day of Feb, 1981, at 10 o'clock 9 m., (signed)
Robert D Leger by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)