CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office Contract No. 395.

Surveyor General's records state:
Set basalt stone 14 x 10 x 8 in stone mound for cor. to secs. 22, 23, 26 & 27.

DIAGRAM

T15S R26E

S22	S23
S27	S26

Description of corner evidence found:

Found stone 14 x 10 x 8 on North edge of stone mound with 2 notches on East edge of stone.

A Pond. Pine, 24 in dia. bears North 37.8', scribes not ledgible. B.L.M. sign, 6-23-59.
A Pond. Pine, 19 in. dia., bears S43°W 38.0', scribed T15S R26 S27, B.T. with B.L.M. B.T. sign, 6-23-59.
No record of either B.T. - old B.T.s, but question if originals.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½" x 30" Alum. pipe with 3" Alum. cap marked as shown:

T15S R26E

S22	S23
S27	S26

RLS 1104 1979

A Doug. Fir, 7 in dia., bears N69°E 37.9', scribed T15S R26E S23, B.T.
A Doug. Fir, 6 in. dia., bears S28°E 59.8', scribed T15S R26E S26, B.T.
A Doug. Fir, 7 in. dia., bears S55°W 62.9', scribed T15S R26E S27, B.T.
A Doug. Fir, 12 in. dia., bears N44°W 62.8', scribed T15S R26E S22, B.T.

Witness to Corner: Michael Yardley
Chainman

REGISTERED
PROFESSIONAL
LAND SURVEYOR
James R. Tye
OREGON
JULY 22, 1977
JAMES R. TYE
1104

I hereby certify the above monument was re-established as herein described on 6-22-79.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of Aug, 19 79, at 1:20 o'clock P m., (signed)
Robert D. Leggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)

R-17