CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Mark A. Fullerton under his General Land Office contract No. 395.

Surveyor General's records state:
Set basalt stone 24 x 14 x 10 in stone mound for corner to sec's. 23, 24, 25, & 26.

DIAGRAM

T15S	R26E
S23	S24
S26	S25

Description of corner evidence found:

Found stone 24 x 14 x 9 in stone mound.

N.A.
For verification measured East to corner to Secs. 24, 25, 19 & 30. Measured distance of 4984± which compares to distance of 4923' by C. Albert White survey (1959-1960) along the South line of Sec. 36.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½" x 30" Alum. pipe with 3" Alum cap marked as shown.
Buried orig. stone next to pipe and built mound around pipe.

T15S	R26E
S23	S24
S26	S25

RLS 1104 1979

A Pond. Pine, 10 in. dia., bears N26°W 108.1', scribed T15S R26E S23, B.T.
A Juniper, 12 in. dia., bears N44°E 89.7' scribed T15S R26E S24, B.T.
A Pond. Pine, 7 in. dia., bears S13°E 90.4', scribed T15S R26E S25, B.T.
A Doug. Fir, 9 in. dia., bears S57°W 191.8', scribed T15S R26E S26, B.T.

Witness to Corner;
Michael Yardley
Chainman

REGISTERED
PROFESSIONAL
LAND SURVEYOR
James R. Tye
OREGON
JULY 22, 1977
JAMES R. TYE
1104

I hereby certify the above monument was re-established as herein described on 7-23-79.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of Aug, 1979, at 1:30 o'clock P.m., (signed)
Robert D Bagett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/66)

R-21