RECORD OF LAND CORNER MONUMENTATION

CORNER: Standard Corner—Secs. 35 & 36, T.15S., R.26E., W.M.

ORIGINAL SURVEY BY: Alonso Gesner

CONTRACT NUMBER: 206

CONTRACT DATE: July 10, 1874

SUBSEQUENT SURVEYS: Mark A Fullerton 1881, C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION: Set stone 14x12x8 for standard cor. to secs. 35 & 36. From which a Pine 12 in. dia. bears S.65°E, 175 lks.

1881 RESURVEY BY MARK A. FULLERTON, U.S. DEPUTY SURVEYOR UNDER HIS CONTRACT NO. 395, DATED 05/25/1881: to stone 14x12x8 in stone mound for standard cor. to secs. 35 & 36.

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 322): SEE RECORD MAP OF SURVEY NO. 58.

The standard cor. of secs. 35 and 36, determined at record bearing and distance from the original bearing tree:

A pine, 30 ins. diam., bears S. 56° E., 175 lks. dist., with T16S and portions of other scribe marks visible on an opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground with brass cap mkd.

S C
T 15 S | R 26 E
S 35 | S 36
1959

from which new bearing trees:

A pine, 12 ins. diam., bears N. 63° E., 31 lks. dist., mkd. T15S R26E S36 SC BT.

A fir, 20 ins. diam., bears N. 52° W., 53 lks. dist., mkd. T15S R26E S35 SC BT.

EVIDENCE FOUND:
None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

PREPARED BY:
Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

January 9. 2017

RECEIVED AND FILED
GRANT COUNTY SURVEYOR
JAN 30 2017
BY: _____

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
JULY 8, 2002
MICHAEL C. SPRINGER
#70918
EXPIRES: 6/30/2018