CERTIFIED RECORD OF LAND CORNER MONUMENTATION

CORNER TO SECTIONS 7 & 18, T15S, R29E, AND TO SECTIONS 12 & 13, T15S, R28E, W.M.

History of original corner establishment: SET BY S.W. LACKLAND UNDER HIS CONTRACT NO. 384, DATED MARCH 29, 1881.

HIS NOTES STATE: SET STONE 16x4x4 IN MOUND OF STONE, FROM WHICH:

A PINE 36 IN. DIA. BEARS S 21°W 82 LKS. DIST.

A PINE 30" IN. DIA. BEARS S84°E 62 LKS. DIST.

DIAGRAM

T15S

R28E | R29E

S12 | S7

S13 | S18

1982

RLS 934

Description of corner evidence found:

FOUND A PARTLY SCATTERED STONE MOUND

ORIG. STONE NOT FOUND.

FND OBT, 36" DBH P. PINE, OPEN FACE W/SCRIBES "T15 BT" VISIABLE, BEARS S 21°W, 54.1 FT.

FND OBT, 36" DBH P. PINE, BADLY WEATHERED, SCRIBES BARELY USIABLE ON OPEN FACE, BEARS S 76°E, 47.5 FT.

THE ORIG. SURVEYOR APPARENTLY MADE A 10 LINK ERROR IN DISTANCE AND READ THE WRONG SIDE OF 80° ON COMPASS, FOR S.E. BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

AT REC. BEARING AND DIST. FROM SW. BT I SET A 3/4" x 30" AL. PIPE WITH A 3½" AL. CAP STAMPED AS SHOWN ABOVE, IN MOUND OF STONE.

MY NEW BT'S:

A 7" DBH P. PINE, SCRIBED "T15S R29E S18BT", BEARS S63°E, 20.5 FT.

A 12" DBH P. PINE, SCRIBED "T15S R29E S7 BT" BEARS N18°E, 41.2 FT.

A 10" DBH P. PINE, SCRIBED "T15S R28E S12 BT" BEARS N26°W, 45.2 FT.

A 9" DBH P. PINE, SCRIBED "T15S R28E S13 BT" BEARS S42°W, 36.6 FT.

DATE SET: 8-26-82

WITNESS: DALE WRIGHT, LOIS MCLIND

REGISTERED PROFESSIONAL LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

Office of ..... County of .....

State of ..... I hereby certify that the within instrument was filed in this office for record on the ..... day of ....., 19.....

..... by .....

(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

J-1