CERTIFIED RECORD OF LAND CORNER MONUMENTATION

¼ Corner to Sections 9 & 16, T15S, R29E, W.M.

History of original corner establishment: Set By S.W. Lackland

under his Contract No. 384 dated March 29, 1881.

His notes state: Set Stone 18 x 6 x 6 in mound of stone

for ¼ Sec. Cor from which:

A pine 10 in dia bears S 35°W 95 lks. dist.

DIAGRAM

T15S R29E

¼ 9/16

1982

RLS 934

Description of corner evidence found:

Fnd OBT, a 18" DBH. P. Pine windfall, partly open face with scribes "¼ S BT" visible, Bears S 35°W 95 lks. = 62.7 ft. (Record)

Description of monument and accessories I established to perpetuate the original location of this corner:

At record bearing and distance from OBT I set a 3" x 30" Al. Pipe with a 3½" Al. Cap stamped as shown above, 9" above ground, in large mound of stone. My new BT's are:

A 13" D.B.H. P. Pine, scribed "¼ S16 BT" Bears S 01°E, 64.2 ft.

A 13½" D.B.H. P. Pine, scribed "¼ S9 BT" Bears N67°W, 28.9 ft.

Date Set: 9-15-82

Witness: Dale Wright, Luis McLind

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 16 day of Dec, 1982

Robert D. Bagett by

(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

T-11