CERTIFIED RECORD OF LAND CORNER MONUMENTATION

CORNER TO SECTIONS 9, 10, 15 & 16, T15S, R29E, W.M.

History of original corner establishment: SET BY S.W. LACKLAND

UNDER HIS CONTRACT No. 384 DATED MARCH 29, 1881

HIS NOTES STATE: SET STONE 15x8x8 IN MOUND OF STONE

FOR COR TO SECS 9, 10, 15 & 16

A FIR 20 IN DIA. BEARS N13°E 68 LKS.

A PINE 28" IN DIA BEARS N40°W 144 LKS.

DIAGRAM

T15S R29E

S9	S10
S16	S15

1982

RLS 934

Description of corner evidence found: NONE FOUND

Description of monument and accessories I established to perpetuate the original location of this corner: I SET CORNER BY DOUBLE PROPORTIONMENT. AT CALCULATED POSITION I SET A 3"x30" AL. PIPE WITH A 3½" AL. CAP STAMPED AS SHOWN. MY NEW BT'S ARE AS FOLLOWS:

A 11" D.B.H. D. FIR, SCRIBED "T15S R29E S16 BT" BEARS S71°W, 27.5 FT.

A 8" D.B.H. D. FIR, SCRIBED "T15S R29E S9 BT" BEARS N43½°W, 15.4 FT.

A 7" D.B.H. D. FIR, SCRIBED "T15S R29E S10 BT" BEARS N69°E, 9.4 FT.

A 12½" D.B.H. TAMARACK, SCRIBED "T15S R29E S15 BT" BEARS S39½°E, 35.5 FT.

DATE SET: 10-7-82

WITNESS: DALE WRIGHT, LOIS McLIND

REGISTERED PROFESSIONAL LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 16 day of Dec, 19 82

Courtney Baggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

T-13