CERTIFIED RECORD OF LAND CORNER MONUMENTATION

CORNER TO SECTIONS 17, 18, 19, & 20, T15S, R29E, WM.

History of original corner establishment: SET BY J. W. LACKLAND UNDER HIS CONTRACT No. 384 DATED MARCH 29, 1881. HIS NOTES STATE: " SET STONE 16x12x6 IN MOUND OF STONE FOR COR TO SECS 17, 18, 19 & 20 FROM WHICH:

A PINE 36 IN DIA. BEARS N42°W 149 LKS. DIST.

A PINE 48 IN DIA BEARS N78°E 90 LKS. DIST.

DIAGRAM

T15S R29E

S18	S17
S19	S20

1982

RLS 934

Description of corner evidence found:

FOUND STONE 15"x9"x6" WITH 5 NOTCHES ON E. CORNER, BURIED 8" IN GROUND WITH 2 SMALLER STONES BESIDE.

OBT, A 26" P. PINE STUMP, 4' HIGH, SCRIBES "BT" VISIBLE ON LOWER BLAZE, BEARS N10°W 99.1 FT.

OBT, A 36" DIA. P. PINE STUMP, 22" HIGH, BADLY ROTTED, BEARS N72°E 56.6 FT.

Description of monument and accessories I established to perpetuate the original location of this corner: IN PLACE OF FOUND STONE I SET A 3"x 30" AL. PIPE WITH A 3½" AL. CAP STAMPED AS SHOWN ABOVE. MY NEW BT's ARE AS FOLLOWS:

A 8" DBH P. PINE, SCRIBED "T15S R29E S17BT" BEARS N8°E, 11.6 FT.

A 8" DBH P. PINE, SCRIBED "T15S R29E S18BT" BEARS N44°W, 26.8 FT.

A 8" DBH P. PINE, SCRIBED "T15S R29E S19BT" BEARS S28½°W, 14.7 FT.

A 11" DBH P. PINE, SCRIBED "T15S R29E S20BT" BEARS S12°E, 18.5 FT.

I BURIED ORIG. STONE ALONGSIDE AL. PIPE.

DATE SET: 8-25-82

WITNESS: DALE WRIGHT, LUIS MCLIND

REGISTERED PROFESSIONAL LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 16 day of Dec, 19 82

Lourta Baggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

N-5